

Technical Data

6.5mm Hybrid

Attributes	Standard	Result
Type of floor covering		Hybrid / Rigid Core
Installation		Drop lock
Core		SPC
Size		1420mm x 180mm
Thickness		6.5mm
Core thickness		5.0mm
Wear layer		0.5mm
Surface treatment		PU coating
Backing		1mm EVA underlay
Packaging		8 Planks / pack = 2.0448m ²
Total weight		10.31kg/m ² / 21.08kg per pack
Beveled edge		4-sided micro bevel
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	Commercial: light Domestic: heavy
Reaction to fire	AS/NZ ISO9239 1-2003	CHF: ≥11kW/m ² Smoke value: 158% min
Slip resistance	AS 4586-2013 Amdt 1-2017 Appendix A	SRV 36 / P3
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	FIIC ^{4,5} = 68 L'nTw ³ = 41 AAAC 5 Star Rating ¹
Underfloor heating		Suitable for hydronic in-slab heating, max. 27°C
Environmental	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC Yes
Quartz content (wt%)		Not detected
Warranty	Commercial Domestic	10 Year wear* 25 Year wear*